

STARCAM - XL

« The **HIGHER** you get, the better the **VIEW** »



The Egripment StarCam XL is the longest version of the Egripment StarCam Tower Product Line. Evolutionary improvements and based on the classic StarCam System with the possibility to use the column either upright or hanging – all in one unit.

The Egripment StarCam XL is made of strong, square aluminum tubes, in combination with stainless steel reinforcement points. The individual elements are guided in square, synthetic bearings, offering high strength with a minimal friction. The sections are connected with non-corrosive steel cables.

The all new StarCam XL has a payload of, 48 kg | 106 lbs when used hanging and up to 60 kg | 132 lbs in normal operation and still fulfills even the strongest safety demands.

The telescoping remotely controlled Electric Column lifts the camera with any Remote Head, such as a HotHead, 301 | 306, Scanner or any other (stabilized) remote head, straight up to a maximum height of 9.25 m | 30.35 ft.

The movement is very smooth and can be used during the shot.

The hand or computer controlled movement is completely proportional, and you can adjust the degree of ramping during the start and stop. Easy to set up end stop for individual top and bottom limits.



STARCAM - XL

The StarCam can easily be operated by one person, by joystick or foot pedal.

Egripment's StarCam XL is very easy and quick to mount in every location, no matter if it stands up ride on a leveling floor cross, a dolly, a flat plate or hanging upside down in the ceiling truss – simply at almost any position.

Optional accessories like bazooka extensions, encoder package in combination with Egripment Tracking Interface for Virtual Studios and Augmented Reality as well as low mode remote brackets complete the StarCam Product Line.



Specifications	Art.: STARCAM XL	
Min Height:	2.35 m	7.70 ft
Max Height:	9.25 m	30.35 ft
Max Speed:	1 m/s	3.3 ft/s
Weight:	143 kg	315 lbs
Load capacity up ride:	60 kg	132 lbs
Load capacity hanging:	48 kg	106 lbs
Voltage:	230 V AC	110 V AC

All data are subject to change without notification.



EGRIPMENT
CAMERA SUPPORT

EGRIPMENT B.V.

Machineweg 22, 1394 AV Nederhorst den Berg, Holland
Phone: +31 294 253988, holland@egripment.com

EGRIPMENT Deutschland GmbH

Immendorfer Straße 1, 50354 Hürth, Deutschland
Phone: +49 2233 6877-0, germany@egripment.com

EGRIPMENT U.S.A.

Phone: +1 (715) 386-0777, usa@egripment.com

www.egripment.com